

# 1980 CHRYSLER OUTBOARD SPECIFICATION

	140 and Charger 140	115 and Charger 115	100 and Charger 100	85 and Charger 85	Charger 85 "Special Edition"	75 and 75 SKIER	55	45
<b>HP @ RPM</b>	140 @ 5250	115 @ 5000	100 @ 5000	85 @ 5000	85 @ 5000	75 @ 4750	55 @ 5000	45 @ 5000
<b>No. of Cylinders</b>	4	4	4	3	3	3	2	2
<b>Piston Displacement, cu. in. (cc)</b>	103 (1688)	99.9 (1637)	96.55 (1582)	72.39 (1186)	69.81 (1132)	72.39 (1186)	49.9 (818)	42.18 (691)
<b>Bore x Stroke, in. (mm)</b>	3 <sup>3</sup> / <sub>8</sub> x 2.87 (85.7 x 73.1)	3 <sup>1</sup> / <sub>8</sub> x 2.8 (85.7 x 71.1)	3 <sup>1</sup> / <sub>8</sub> x 2.8 (84.1 x 71.1)	3 <sup>1</sup> / <sub>16</sub> x 2.8 (84.1 x 71.1)	3 <sup>1</sup> / <sub>16</sub> x 2.8 (84.1 x 68.6)	3 <sup>1</sup> / <sub>16</sub> x 2.8 (84.1 x 71.1)	3 <sup>1</sup> / <sub>8</sub> x 2.8 (85.7 x 71.1)	3 <sup>1</sup> / <sub>8</sub> x 2.75 (79.4 x 69.8)
<b>Net Weight, lbs. (kgs)</b>	140: 297 (135) C140: 302 (137)	115: 295 (134) C115: 300 (136)	100: 295 (134) C100: 300 (136)	85: 270 (123) C85: 275 (125)	271 (123)	75: 270 (123) 75 Skier: 275 (125)	183 (83.1)	148 (67.1)
<b>RPM Range, Full Throttle</b>	5000- 5500	4500- 5500	4500- 5500	4500- 5500	4500- 5500	4400- 5100	4500- 5500	4500- 5500
<b>Std. Prop.</b>	13 x	13 x	13 x	13 x	13 x	13 x	11 <sup>3</sup> / <sub>8</sub> x	10 <sup>1</sup> / <sub>8</sub> x